



SAPHIR® AS

SAPHIR® is our range of polycarbonate coated sheet.

SAPHIR® AS, is an antistatic coated polycarbonate sheet with a unique protection against electrostatic charging.

SAPHIR® AS is a polycarbonate sheet with a two side anti-static coating.

The coating gives an effective protection against electrostatic charging and prevents dust and dirt attraction.

SAPHIR® AS prevents electrostatic discharge (ESD) and the high impact strength of polycarbonate is combined with excellent fire properties and optical clarity.

SAPHIR® AS is to be used in flat applications.

SAPHIR® AS BENEFITS:

- Protection against electrostatic charging
- Prevent dust and dirt attraction
- Impact Resistant
- More than 10 times the impact strength of high impact PMMA

APPLICATION AREAS:

SAPHIR® AS is suitable for hoods and inspection glazing for testing equipment.

In applications where it is important to prevent electrostatic build up, such as explosive atmospheres.

DELIVERY PROGRAM:

Standard size: 2000 x 3000 mm

Thickness range: 3 – 12 mm

2 sides coated

Special sizes and thicknesses on request

SAPHIR® AS TECHNICAL SPECIFICATIONS

Property	Value	Unit	Standard
Physical properties			
Density	1,2	g/cm ³	ISO 1183
Refractive index (20 °C)	1,586		ISO 489
Moisture absorption 24 hours, 23 °C, 50% RH	0,15	%	ISO 62
Mechanical properties			
Tensile strength at yield (at break)	60 (70)	N/mm ²	ISO 527
Elongation at yield (at break)	6 (110)	%	ISO 527
Elastic modulus	>2300	N/mm ²	ISO 527
Flexural modulus	>2300	N/mm ²	ISO 178
Charpy unnotched impact strength -40 °C	NB	kJ/m ²	ISO 179/1eU
Charpy notched impact strength -30 °C	11	kJ/m ²	ISO 179/1eA
Izod notched impact strength +23 °C	65	kJ/m ²	ISO 180/1A
Izod notched impact strength -30 °C	10	kJ/m ²	ISO 180/1A
Thermal properties			
Linear coefficient of thermal expansion (20-70 °C)	65x10 ⁻⁶	K ⁻¹	ISO 11359-2
Thermal conductivity	0,20	W/m.K	DIN 8302
Optical properties			
Colour	Clear (slightly blue)		
Coating properties			
Surface resistance	10 ⁴ – 10 ⁸	Ω	ASTM D257
Additional Information			
The surface of the material should be grounded to allow static dissipation.			

Properties reported here are typical values. Arla Plast makes no representation that the material in any particular shipment will conform exactly to the values given. The above information is based upon experience and given in good faith. Due to many factors which are outside our knowledge and control, no warranty is given or is to be implied with respect to such information. Detailed product specification and technical manual/information is available on request.